




裸圧着端子 (A形)



棒状形端子

UL	SR	呼び	在庫	タイプ	各部の寸法						適合電線範囲			適合工具	一箱入数		
					B	H	L	F	E	D	d ₁	板厚	単線mm			撚線mm ²	AWG
		A-0.3			1.0	1.0	14.0	10.0	4.0	2.3	0.8	0.65	0.32~0.6	0.1~0.3	26-24	DS031, DH-1B AC-5N-D	1,000
		A-0.5								1.2	0.5	0.5~0.8	0.2~0.5	24-20			
		A-1.25			1.7	1.7	17.0	12.7	4.3	3.4	1.7	0.8	0.57 ∩ 1.44	0.25 ∩ 1.65	22-16	DS031 ミ12 5N18 DH-1B AC-5N-D	
		A-1.25N			1.3	1.3	17.5	13.2									
		A-1.15L			1.6	1.4	21.3	17.0	4.3	4.2	2.3	0.8	1.14 ∩ 1.82	1.04 ∩ 2.63	16-14	ミ12, 5N18 214A, DH-1B AC-5N-D REC-14A	
		A-1.25LB			1.7	1.7											
		A-2			1.6	1.6	17.0	12.7	4.3	4.2	2.3	0.8	1.14 ∩ 1.82	1.04 ∩ 2.63	16-14	ミ12, 5N18 214A, DH-1B AC-5N-D REC-14A	
		A-2L			1.4		21.3	17.0									
		A-2LB			1.7	1.7											
		A-5.5			2.0	2.0	21.0	14.7	6.3	5.6	3.4	1.0	1.82 ∩ 2.89	2.63 ∩ 6.64	12-10	5N18, 214A DH-1B AC-5N-D REC-14A	
		A-5.5L					25.8	19.5									
		A-5.5LL					30.3	24.0									
		A-8D			3.5	3.5	33.5	25.2	8.3	7.1	3.5	1.2	1.82~2.89	2.63~6.64	12-10	5N18, 214A REC-14A	300
		A-8									4.5			2.89~3.65			
		A-14S			4.5	4.5	40.5	30.5	10.0	9.0	5.8	1.6	3.65~4.62	10.52~16.78	6	214A, 9H-60, 9H-150 REC-14A, REC-60F REC-150F, REC-1520*	200
		A-14															
		A-22S			3.5	3.5	47.0	35.6	11.4	11.5	7.7	1.8	4.62~5.81	16.78~26.66	4	9H-60, 9H-150 REC-60F, REC-150F REC-1520*	100
		A-22			6.5	6.5											
		A-38			6.9	6.9	50.0	37.0	13.0	13.3	9.4	2.0	5.81~7.34	22.66~42.42	2		50
		A-60					55.0			18.0	15.5		11.4	7.34~8.26			

- 各呼びの印は、UL登録品、CSA登録品です。
- UL登録品又はCSA登録品としてご使用の際は、注文時にご指示ください。カートンがUL品用又はCSA品用となります。
- 上記寸法表にかぎらず特注品もご相談ください。
- 適合工具欄のREC-1520*は、REC-1520FH、REC-1520FMHの2機種があります。
(注1 . 9H-60, 9H-150, 12号H, 12号A, REC-60F, REC-150F, REC-1520*)

棒状形端子は通常の電流よりも60%~70%位の目安でご使用ください。