

絶緣被覆付圧着端子(AVH·APH/BVH·BPH形)











ホック形端子

	<u> </u>			在		呼び		各 部 の 寸 法						標準	適合電線範		囲	適合工具	一箱		
	Š	(P)	ビニル	庫	(3)	ナイロン	庫	d_2	В	d ₁	F ₁	Q 2	Q	L ₁	板厚	色	単線mm	撚線mm ²	AWG	旭百上县	入数
ストレー ト形			AVH1.25-3			APH1.25-3		3.2	5.5		6.6		13.8	18.8		3 赤	0.8 \$ 1.44	0.5 \$ 1.65	20-16	DH-1B	
			AVH1.25-4			APH1.25-4		4.3	8.0	3.3	3 7.3	9.5	15.8	20.8	3 0.8						1,000
			AVH1.25-5			APH1.25-5		5.3	0.0	5.5			10.0	20.0							
			AVH1.25-6			APH1.25-6		6.4 11.5		10.0		20.2	25.2						AC-5N-D	500	
			AVH2-3			APH2-3		3.2	8.0				16.8	21.8			1.14	1.04 \$ 2.63	16-14	4号D 34号 34S DH-1B AC-5N-D	500
			AVH2-4			APH2-4		4.3	8.5		8.3	3		21.0							
			AVH2-5			APH2-5		5.3	9.5	3.9		9.5	17.7	22.7	0.8	青					
			AVH2-6			APH2-6		6.4	12.0		11.5		22.0	27.0			1.02				
			AVH2-8			APH2-8															
			AVH3.5-4			APH3.5-4		4.3	8.5	4.9	8.3	14.0	17.8	26.5	1.0	黄	1.82 ~ 2.4	2.63 ~ 4.6	12		500
			AVH5.5-4			APH5.5-4	4.3	9.5		10.2	2	21.3	29.0			4.00	0.00		5号	400	
			AVH5.5-5			APH5.5-5	6 8	5.3			13.5					黄	1.82 \$ 2.89	2.63 \$ 6.64	12-10	DH-1B AC-5N-D	
			AVH5.5-6			APH5.5-6		6.4	12.0				25.8	33.5							300
			AVH5.5-8			APH5.5-8		8.4	15.0				27.3	35.0							
拡管形			BVH1.25-3			BPH1.25-3 BPH1.25-4	3.2	5.5		6.6		13.8	18.3			0.8	0.5		3号D 34号		
			BVH1.25-4					4.3	8.0	(4.0)	7.3	9.0	15.8	20.3		.8 赤	0.8 \$ 1.44	0.5 \$ 1.65	20-16		1,000
			BVH1.25-5			BPH1.25-5	\vdash	5.3						0.1=							===
			BVH1.25-6			BPH1.25-6		6.4	11.5		10.0		20.2	24.7							500
			BVH2-3			BPH2-3		3.2	8.0		11.5	9.0	16.8	21.3		青	1.14 \$ 1.82	1.04 \$ 2.63	16-14	4号D 34号 34S DH-1B AC-5N-D	
			BVH2-4			BPH2-4		4.3 5.3	8.5 9.5	4.7			17.7	20.0							500
			BVH2-5			BPH2-5		6.4	9.5	(4.5)			17.7	22.2							
			BVH2-6 BVH2-8			BPH2-6 BPH2-8		8.4	12.0				22.0	26.5							
			BVH3.5-4					4.3	8.5	6.0	8.3	13.5	17.8	26.0	1.0	带	1.82 ~ 2.4	263~16	12		500
			BVH5.5-4			-		4.3	0.0		10.2	13.5	17.0	20.0	1.0	0 黄	1.82	2.63 \$ 6.64		5号 DH-1B AC-5N-D	300
			BVH5.5-5			-		5.3	9.5				21.3	28.5							400
			BVH5.5-6			-		6.4		6.4	-		25.8	33.0							
			BVH5.5-8			_		8.4	15.0	-	13.5		27.3	34.5							300

- 1. 各呼びの 印は、UL登録品、CSA登録品です。 2. UL登録品又はCSA登録品としてご使用の際は、注文時にご指示ください。カートンがUL品用又はCSA 品用となります。
- 3. ()はBPH形の寸法です。